

Hydraulic drive series	3.9m	5.8m	6m	8m	narrow 8m	10m	12m	14m
Model: (Hydraulic drive)	JCPT 0607 HD	JCPT 0807 HD	JCPT 0808 HD	JCPT 1012 HD	JCPT 1008 ZHD	JCPT 1212 HD	JCPT 1412 HD	JCPT 1614 HD
S. W. L	240KG	230 KG	380 KG	450 KG	230 KG	320 KG	320 KG	227 KG
S.W.L on extensin	100KG	113 KG	113 KG	113 KG	113 KG	113 KG	113 KG	113 KG
Max. working height	5.9M	7.8M	8M	10M	10M	12M	13.8M	15.70M
Max. platform height	3.9M	5.8M	6M	8M	8M	10M	11.80M	13.70M
Overall length	1.44M	1.83M	2.435M	2.435M	2.435M	2.435M	2.435M	2.84M
Overall width	0.76M	0.81M	0.81M	1.15M	0.81M	1.15M	1.15M	1.39M
Overall height (rails up)	2.03M	2.1M	2.20M	2.32 M	2.32 M	2.44 M	2.58 M	2.59 M
Overall height (rails down)	1.67M	2.05M	1.87M	1.78M	1.89 M	1.92M	2.04 M	2.05 M
Platform size	1.29M*0.70M	2.635M*0.75M	2.27M*0.8M	2.27M*1.12M	2.27M*0.81M	2.27M*1.12M	2.27M*1.12M	2.64M*1.12M
Platform extension	0.6M	0.9M	0.9M	0.9M	0.9M	0.9M	0.9M	0.9M
Lift motor	24V/1.2KW	24V/3.3W	24V/3.3W	24V/3.3W	24V/3.3W	24V/3.3W	24V/3.3W	24V/4.5W
Travel speed (stowed)	4KM/H	3.5KM/H	3.5KM/H	3.5KM/H	3.5KM/H	3.5KM/H	3.5KM/H	3.5KM/H
Travel speed (raised)	0.5KM/H	0.8KM/H	0.8KM/H	0.8KM/H	0.8KM/H	0.8KM/H	0.8KM/H	0.8KM/H
Up/down speed	32/27SEC	18/22SEC	24/54SEC	28/38SEC	28/40SEC	45/36SEC	84/38SEC	88/60SEC
Battery	2*12V*115AH	4*6V/225AH	4*6V/225AH	4*6V/225AH	4*6V/225AH	4*6V/225AH	4*6V/240AH	4*12V/300AH
Charger	24V/10A	24V/25A	24V/25A	24V/25A	24V/25A	24V/25A	24V/25A	24V/25A
Max dimbing ability	30%	25%	25%	25%	25%	25%	25%	25%
Work maximum	2°/3°	1.5°/3°	2°/3°	2°/3°	2°/3°	2°/3°	1.5°/3°	2°/3°
Tire size	∅ 323MM*100MM	∅ 305MM*100M	∅ 381MM*127M	∅ 381MM*127M	∅ 381MM*127M	∅ 381MM*127M	∅ 381MM*127M	∅ 381MM*127M
G.W	920KG	1475KG	1970KG	2240KG	2015KG	2500KG	2880KG	3280KG